



Speedlite Transmitter ST-E3-RT Specification Sheet

Flash modes		
	Auto exposure control	E-TTLII/E-TTL
	High speed sync (FP)	Yes
	Manual / output settings	Yes - 1/1- 1/128
	Manual steps	1/3 step
	Strobe / output settings	Yes - 1/4-1/128
	Frequency	1-500Hz (199Hz using optical slave function)
Flash-related function		
	FE lock	Yes
	Flash exposure compensation	Yes
	Flash exposure bracketing	Yes
	Second-curtain flash sync	Yes
	Modelling flash	Yes
	Colour temperature info communication	No
Wireless flash		
	Transmitter	Yes
	Transmission type	Radio
	Transmitter Max range approx	Indoors: 30m Outdoors: 30m
	Slave	No
	No of groups	5
	No of channels	15
	Remote Shutter Release	Yes
AF Assist		
	AF-assist beam	No
Power source		
	Battery	2 x AA batteries
	External power supply	No
Construction		
	Dust and water resistance	Yes
	Mounting foot material	Metal
Misc.		
	Custom function	8 (3 personal functions)
	Flash settings from camera menus ²	No
	PC terminal	No
	Compatible Accessories	SPEEDLITE 600EX-RT
	Dedicated flash bracket	No
Dimensions & weight		
	Size (W x H x D), mm	67.4 x 61.5 x 77.4 ³
	Weight (Excluding batteries), grams	110g

All data is based on Canon standard testing methods except where indicated.
Subject to change without notice.

[1] Time taken to recharge flash after full discharge using Alkaline AA batteries

[2] With compatible cameras only

[3] Except for the dust and water prevention adaptor